

NEW



SWBA®

HEED 3 - SWBA
300-003A-SW



MADE IN USA

HEED 3 - SWBA® units are proudly designed and made in the United States of America by Submersible Systems, an ISO 9001:2015 Certified company with over 45 years manufacturing experience.



TYPE APPROVED

HEED 3 - SWBA® is first to the market with a type-approved device under the global *Good Practice Guideline - Swiftwater Breathing Apparatus*.



MOLLE MOUNT

Our SWBA® package comes with a type-approved mounting system that can be fitted to most rescue type personal floatation devices. The mounting system also has attachment systems for velcro badges and a chemical light stick.

SAVING LIVES

**SUBMERSIBLE
SYSTEMS, INC.**

FOR OVER 45 YEARS

WHY USE SWBA®?

According to NFPA, a firefighter is **four times more likely to lose their life in a water rescue** than in structural firefighting. SWBA provides operators a higher level of safety.



More Air

3 cu ft / 85 liters of air gives approximately 57 breaths of air. At surface level, this can last several minutes.



Less Risk

Minimizes inhalation or ingestion of flood water contaminants.



More Time

Provides more window of time to survive, be rescued or carry out critical tasks.



www.heed3.com



Huntington Beach, California, USA



+1•714•842•6566



SWBA® PACKAGE

- HEED 3 - SWBA® 300
 - 3 cu ft / 85L aluminum cylinder
 - 36" flexible braided hose
 - 1st and 2nd Stage Regulators
- SWBA® Mounting System
- SWBA® Velcro Patch

AVAILABLE OPTIONS

- DOT 3AL 3000 or ISO marked cylinder
- SCUBA (Yoke) cylinder fill adapter
- DIN cylinder fill adapter
- Air compressor refill adapter
- Hand-pump
- Portable electric compressors
- Nose Clip (with Lanyard)

HEED 3 - SWBA® 300 Specifications

Part Number: 300-003A-SW

Cylinder Capacity: 3 cu ft / 85 liters

Service Pressure: 3000 psi / 207 bar

Length: 14" / 35 cm

Diameter: 2.5" / 6.4 cm

Weight: 2.5 lb. / 1.1 kg

Cylinder Material: Aluminum - Black Anodized

Regulator Type: Piston, downstream demand valve,
36" flexible braided hose

Pressure Relief: Integrated in regulator

Operational Temperature: -22°F / -30°C < +158°F / +70°C

Duration of Air: 57 breaths*

*Based on 1.5 liters per breath



HEED 3 - SWBA® Approved Training

SWBA Awareness, Operator, Specialist and Instructor training available through www.swba.tech



User Guides

User guides and service manuals are available at our website www.heed3.com



www.heed3.com



Huntington Beach, California, USA



+1•714•842•6566